

## Label Printing Scale



### KEY PARAMETERS

- ◆ **Precision**  
1/3000
- ◆ **Weighing scope**  
0-6Kg-15Kg or 0-15-30Kg
- ◆ **Weighing Resolution (e)**  
2/5 g or 5/10 g
- ◆ **Storage Capacity**  
10000 PLUs
- ◆ **Display**  
Double sides displays with the pole, 26 LED Display.
- ◆ **Keyboard**  
140 keys (112x2=224 PLU Hot-keys, 28 Function keys)
- ◆ **Printing Type**  
Thermal Printing , Printing Speed: >50mm/s, Printing Width : 56mm (MAX),
- ◆ **Label Paper Roll**  
Width (Max) : 58±0.5mm, Outer diameter 80 mm (Max) , internal Diameter : 40 mm (Min)
- ◆ **Label Size**  
Width : 30 mm-58mm, Length 25mm-48mm, Recommended label size : 58mm(W)x37mm(L)
- ◆ **Communications Ports**  
1xRS232 , 1XRJ45 Ethernet
- ◆ **Power Supply**  
AC 100-120V or AC 200-240V 50/60 Hz 0.5A
- ◆ **Build-in-battery**  
Without
- ◆ **Dimension(MM)**  
360 (w) X 440(D) X 175(H) (The Height is 490 mm including display pole)
- ◆ **Net weight**  
About 8.5 kg
- ◆ **Work environment**  
Temperature :- 10°C-40°C , Humidity : 20 % - 90 % RH
- ◆ **Storage Environment**  
Temperature :- 20°C-50°C , Humidity : 10 % - 95% RH

### Function & Features

Big storage capacity :10,000 plus data storage capacity, plus extra storage optional

224 (112X2)PLU hot-keys, easy for calling out the products, computer setting and printing hot-keys

Different type of selling : weighing , default price and weight selling

Could set print parameters, barcode formats according customized.

Support automatic printing

Powerful Network communication : Programme setting , multiple-machine network, back-office management via RS-232 OR Ethernet (TCP/ip)

Easy programming: PLUs database, label barcode format, systems parameters, hot-keys, 8 letter strings, 255 explanations to be edited in pc or directly in scale.

Various special selling modes : discount in percentage or coupon, additional charge in percentage or other extra charge, change price anytime ect